

**Philosophy 240**  
***Symbolic Logic***

**Russell Marcus**  
**Hamilton College**  
**Fall 2011**

Class 23 - Translation into Predicate Logic II (§3.2)

# More than One Quantifier

- If anything is damaged, then everyone in the house complains.
  - ▶  $(\exists x)Dx \supset (\forall x)[(Ix \cdot Px) \supset Cx]$
- Either all the gears are broken, or a cylinder is missing.
  - ▶  $(\forall x)(Gx \supset Bx) \vee (\exists x)(Cx \cdot Mx)$
- Some philosophers are realists, while other philosophers are fictionalists.
  - ▶  $(\exists x)(Px \cdot Rx) \cdot (\exists x)(Px \cdot Fx)$
- It's not the case that all conventionalists are logical empiricists if and only if some holists are conventionalists.
  - ▶  $\sim [(\forall x)(Cx \supset Lx) \equiv (\forall x)(Hx \supset Cx)]$

# Monadic and Relational Predicate Logics

- Predicate logic is monadic if the predicates only take one singular term.
- When predicates take more than one singular term, we call the predicates relational.
- Andrés loves Beatriz
  - Monadic:  $L a$
  - Relational:  $L a b$ 
    - ‘ $Lxy$ ’:  $x$  loves  $y$ :
- Relational predicates will allow us greater generality.
- We will look to reveal as much logical structure as we can.

# Extensions of Monadic Predicate Logic

- Full First-Order Predicate Logic
- A specific predicate for identity
- Functors
- Second-order quantifiers  
(predicate variables)

# Names of Languages We Will Study

- ▶ **PL**: Propositional Logic
- ▶ **M**: Monadic (First-Order) Predicate Logic
- ▶ **F**: Full (First-Order) Predicate Logic
- ▶ **FF**: Full (First-Order) Predicate Logic with functors
- ▶ **S**: Second-Order Predicate Logic

# Languages and Systems of Deduction

- With PL, we used one language, and one set of inference rules.
- But we can use the same language in different deductive systems, and we can use the same deductive system with different languages.
- We will use **M** and **F** with the same deductive system.
- Then, we will introduce a new deductive system using the language **F**, adding new rules covering a special identity predicate.

# Vocabulary of M

- Capital letters A...Z used as one-place predicates
- Lower case letters for singular terms
  - a, b, c,...u are used as constants.
  - v, w, x, y, z are used as variables.
- Five connectives:  $\sim$ ,  $\bullet$ ,  $\vee$ ,  $\supset$ ,  $\equiv$
- Quantifier symbols:  $\exists$ ,  $\forall$
- Punctuation: ( ), [ ], { }

# On Scope

- $(\forall x)(Px \supset Qx)$   
Every P is Q
- $(\forall x)Px \supset Qx$   
If everything is P, then x is Q
- The difference between these two expressions is the scope of the quantifier.



# Scope of a Negation

(in propositional logic)

The **scope of a negation** (in **PL**) is whatever directly follows the tilde.

- ▶ If what follows the tilde is a single propositional variable, then the scope of the negation is just that propositional variable.
- ▶ If what follows the tilde is another tilde, then the scope of the first (outside) negation is the scope of the second (inside) negation plus that inside tilde.
- ▶ If what follows the tilde is a bracket, then the entire formula which occurs between the opening and closing of that bracket is in the scope of the negation.

$\sim\{(P \cdot Q) \supset [\sim R \vee \sim\sim(S \equiv T)]\}$

# Scope of a Quantifier

If what follows the quantifier is a bracket, then any formulas that occur until that bracket is closed are in the scope of the quantifier.

If what follows the quantifier is a tilde, then the tilde and every formula in its scope is in the scope of the quantifier.

If what follows the quantifier is another quantifier, then the inside quantifier and every formula in the scope of the inside quantifier is in the scope of the outside quantifier.

# Quantifier Scope Example

$$(\forall w)\{Pw \supset (\exists x)(\forall y)[(Px \cdot Py) \supset (\exists z)\sim(Qz \vee Rz)]\}$$

- $(\forall w)$ 
  - $\{Pw \supset (\exists x)(\forall y)[(Px \cdot Py) \supset (\exists z)\sim(Qz \vee Rz)]\}$
- $(\exists x)$ 
  - $(\forall y)[(Px \cdot Py) \supset (\exists z)\sim(Qz \vee Rz)]$
- $(\forall y)$ 
  - $[(Px \cdot Py) \supset (\exists z)\sim(Qz \vee Rz)]$
- $(\exists z)$ 
  - $\sim(Qz \vee Rz)$

# Binding

- Quantifiers bind every instance of their variable in their scope.
- A **bound variable** is attached to the quantifier which binds it.
  1.  $(\forall x)(Px \supset Qx)$
  2.  $(\forall x)Px \supset Qx$ 
    - ▶ In 1, the 'x' in 'Qx' is bound.
    - ▶ In 2, the 'x' in 'Qx' is not bound.
- An unbound variable is called a **free variable**.
  3.  $(\forall x)Px \vee Qx$
  4.  $(\exists x)(Px \vee Qy)$ 
    - ▶ In 3, 'Qx' is not in the scope of the quantifier, so is unbound.
    - ▶ In 4, 'Qy' is in the scope of the quantifier, but 'y' is not the quantifier variable, so is unbound.

# Open and Closed Sentences

- Wffs that contain at least one unbound variable are called **open sentences**.
  - ▶  $Ax$
  - ▶  $(\forall x)Px \vee Qx$
  - ▶  $(\exists x)(Px \vee Qy)$
  - ▶  $(\forall x)(Px \supset Qx) \supset Rz$
- If a wff has no free variables, it is a **closed sentence**, and expresses a **proposition**.
  - ▶  $(\forall y)[(Py \cdot Qy) \supset (Ra \vee Sa)]$
  - ▶  $(\exists x)(Px \cdot Qx) \vee (\forall y)(Ay \supset By)$
- Translations from English into **M** should ordinarily yield closed sentences.

# Formation Rules for Wffs of M

1. A predicate (capital letter) followed by a constant or variable (lower-case letter) is a wff.
2. For any variable  $\beta$ , if  $\alpha$  is a wff that does not contain either ' $(\exists\beta)$ ' or ' $(\forall\beta)$ '
  - ▶ then ' $(\exists\beta)\alpha$ ' and ' $(\forall\beta)\alpha$ ' are wffs.
3. If  $\alpha$  is a wff, so is  $\sim\alpha$ .
4. If  $\alpha$  and  $\beta$  are wffs, then so are:
  - ▶  $(\alpha \cdot \beta)$
  - ▶  $(\alpha \vee \beta)$
  - ▶  $(\alpha \supset \beta)$
  - ▶  $(\alpha \equiv \beta)$
5. These are the only ways to make wffs.

# Atomic Formulas

## Subformulas

- A wff constructed only using rule 1 is called an **atomic formula**.
  - ▶ Pa
  - ▶ Qt
  - ▶ Ax
- A wff that is part of another wff is called a **subformula**.
- In ' $(Pa \cdot Qb) \supset (\exists x)Rx$ ', the following are all subformulae:
  - ▶ Pa
  - ▶ Qb
  - ▶ Rx
  - ▶  $(\exists x)Rx$
  - ▶  $Pa \cdot Qb$

# Main Operators

- Quantifiers and connectives are called **operators**, or logical operators.
  - ▶ Atomic formulas lack operators.
  - ▶ The last operator added according to the formation rules is called the **main operator**.



# Overlapping Quantifiers

- Not allowed
- $(\exists x)[Px \cdot (\forall x)(Qx \supset Rx)]$ 
  - ill-formed